



CONTROL APPLICATIONS Ltd.

Supervision & control system

Tel: +972-3-6474998 Fax: +972-3-6474598 24a Habarzel St. Tel-Aviv, 69710, Israel

Elnet Pico 5/60 – Measurement & Display (scaling factor 1)

Measurement Parameter	Display Range in direct connection (scaling factor 1)	Measuring in direct connection (scaling factor 1)	Display Range
Current 5/60	0.0001 – 6A / 0.0001 – 72A	0.0001 – 6A / 0.0001 – 72A	0.0001 – 99999 KA
Neutral Current (calculated) 5/60	0.0001 – 6A / 0.0001 – 72A	0.0001 – 6A / 0.0001 – 72A	0.0001 – 99999 KA
Voltage L-N	0.0001 – 650 V	0.0001 – 650 V	0.0001 – 99999 KV
Voltage L-L	0.000 – 650 V	0.000 – 650 V	0.0001 – 99999 KV
Frequency (Hz)	45 - 65 Hz	45 - 65 Hz	45.001-65.001 Hz
Active power total\phase			0.0000W – 99999 KW
Reactive power total\phase			0.0000VAR - 99999KVAR
Apparent power total\phase			0.0000VA -99999 KVA
Power Factor (cap.\ind.)	-1.0000 ÷ 1.0000	-1.0000 ÷ 1.0000	-1.0000 ÷ 1.0000
Active Energy total\phase			0.000001WH – 9999999 KWH
Reactive Energy total\phase			0.000001VARH - 9999999 KVARH
Apparent Energy total\phase			0.000001VAH - 9999999 KVAH