

CHARACTERISTICS

Ambient temperature	-10 ÷ -70 °C	
Fluid	filtered air 50 µm, with or without lubrication	
Commutation system	poppet	
Max pressure	10 bar	
Connections	G1/8	G1/4
Nominal bore (mm)	2,3	8
Nominal flow rate (NL/min)	98	800
PNEUMATIC FOOT VALVE:		
Valve body	zamak	
Foot valve lever	aluminium	
Pedal body and protection	plastic material with reinforcing steel plate	
Seals	oil and wear resistant compound	
Spool	aluminium	
SOLENOID FOOT VALVE		
Valve body, foot valve lever, protection	dielectric plastic material	



Pneumatic foot valve G1/4 with protection

	<input checked="" type="checkbox"/> Spring return	<input checked="" type="checkbox"/> Bistable	<input checked="" type="checkbox"/> With safety control
	AM-5000		AM-5003
	AM-5001		AM-5004
	AM-5002		AM-5005
<input checked="" type="checkbox"/> External operation - Spring return		<input checked="" type="checkbox"/> External operation - bistable	
	AM-5021		AM-5031
		<input checked="" type="checkbox"/> External operation with safety control	
			AM-5041

Pneumatic foot valve G1/4 without protection

	<input checked="" type="checkbox"/> Spring return	<input checked="" type="checkbox"/> Bistable
	AM-5000A	
	AM-5001A	

Pneumatic foot valve G1/8 with protection

	<input checked="" type="checkbox"/> Spring return		Solenoid foot valve
	AM-5043		AM-5050 No electrical microswitch
	AM-5043B		AM-5051 Electrical microswitch
	AM-5043C		AM-5052 Double electrical microswitch
	AM-5043D		
Version without protection available upon request			