

Braided sleeving


Material : Polyester PET HB
 Temperature range : -50 °C up to +150 °C
 Melting temperature : +250 °C
 Color : Black



Typenr.	Bundle diameter (mm)	Packing (mtr)
Braided sleeving PG 3 mm	3,00 - 7,00	100
Braided sleeving PG 4 mm	4,00 - 10,00	100
Braided sleeving PG 5 mm	5,00 - 10,00	100
Braided sleeving PG 8 mm	8,00 - 11,00	100
Braided sleeving PG 10 mm	10,00 - 15,00	100
Braided sleeving PG 12 mm	12,00 - 19,00	50
Braided sleeving PG 15 mm	15,00 - 27,00	50
Braided sleeving PG 20 mm	20,00 - 28,00	50
Braided sleeving PG 25 mm	25,00 - 34,00	25
Braided sleeving PG 30 mm	30,00 - 37,00	25
Braided sleeving PG 40 mm	40,00 - 45,00	25
Braided sleeving PG 50 mm	50,00 - 65,00	25

Wrapping bands

Material : Polyethylene
 Temperature range : -50 °C up to +85 °C
 Colors : Black and natural



Typenr.	Inside diameter (mm)	Outside diameter (mm)	W (mm)	Bundle diameter (mm)	Packing (mtr)
GST-4	5,0	6,0	7,0	4,0 - 50,0	10,0
GST-6	7,0	8,0	10,8	6,0 - 60,0	10,0
GST-8	8,5	10,0	11,4	7,5 - 60,0	10,0
GST-9	10,2	12,0	13,9	9,0 - 65,0	10,0
GST-12	13,0	15,0	15,0	12,0 - 70,0	10,0
GST-15	16,4	19,0	18,2	15,0 - 100,0	10,0
GST-20	21,0	24,0	19,6	20,0 - 130,0	10,0

Hook and loop tape

Color : Black



Typenr.	Width (mm)	Packing (mtr)
Hook and loop tape back to back 12 mm	12,0	25
Hook and loop tape back to back 20 mm	20,0	25
Hook and loop tape back to back 25 mm	25,0	25
Hook and loop tape back to back 50 mm	50,0	25

Corrugated tubing PA6

Material : Polyamide 6
 Protection rating : IP 68
 Flame class : UL 94 HB
 Temperature range : -40 °C up to +120 °C
 : short term +150 °C



On request also slotted and in Polypropylene available

Applications:

Machine and plant constructions, automotive, shipbuilding, automation, electrical installations.

Mechanical protection for cables and conductors, pressure and impact resistant, flexible, high tensile and compressive strength.

Typenr.	DN	Inside diameter (mm)	Outside diameter (mm)	Bending radius (mm)	Packing (mtr)
Corrugated tubing DN 7,5	7,5	6,9	9,9	13,0	50
Corrugated tubing DN 8,5	8,5	8,4	11,4	15,0	50
Corrugated tubing DN 10,0	10,0	9,9	13,0	20,0	50
Corrugated tubing DN 12,0	12,0	12,2	15,7	30,0	50
Corrugated tubing DN 13,0	13,0	12,7	15,8	35,0	50
Corrugated tubing DN 14,0	14,0	14,2	18,5	40,0	50
Corrugated tubing DN 16,0	16,0	14,9	18,9	40,0	50
Corrugated tubing DN 17,0	17,0	16,6	21,2	45,0	50
Corrugated tubing DN 22,0	22,0	21,2	25,5	50,0	50
Corrugated tubing DN 23,0	23,0	23,2	28,3	55,0	50
Corrugated tubing DN 26,0	26,0	25,7	32,2	60,0	50
Corrugated tubing DN 29,0	29,0	29,0	34,5	65,0	25
Corrugated tubing DN 36,0	36,0	36,0	42,4	90,0	25
Corrugated tubing DN 50,0	50,0	48,1	53,8	100,0	25
Corrugated tubing DN 56,0	56,0	56,3	67,2	130,0	30
Corrugated tubing DN 65,0	65,0	62,7	73,5	145,0	10
Corrugated tubing DN 70,0	70,0	67,5	80,0	160,0	10
Corrugated tubing DN 95,0	95,0	91,5	106,0	210,0	10