

AF09 ... AF38 3-pole contactors

4 to 18.5 kW

AC / DC operated



AF09-30-10




AF26-30-00

AF09 ... AF38 contactors are mainly used for controlling 3-phase motors and power circuits up to 690 V AC and 220 V DC. These contactors are of the block type design with 3 main poles.

- control circuit: AC or DC operated with electronic coil interface accepting a wide control voltage range (e.g. 100...250 V AC and DC), only 4 control voltage ranges covering 24...500 V 50/60 Hz and 20...500 V DC
 - can manage large control voltage variations
 - reduced panel energy consumption
 - very distinct closing and opening.
- built-in surge suppression
- add-on auxiliary contact blocks for front or side mounting and a wide range of accessories.

IEC	UL/CSA		Rated control circuit voltage Uc min. ... Uc max.	Auxiliary contacts fitted		Type	Order code	Weight					
	Rated operational power 400 V AC-3 kW	3-phase motor rating 480 V hp		General use rating 600 V AC A	V 50/60 Hz V DC								
4	25	5	25	24...60	20...60 (1)	1 0	AF09-30-10-11	15BL137001R1110	0.270				
							0 1	AF09-30-01-11	15BL137001R1101	0.270			
				48...130	48...130	1 0	AF09-30-10-12	15BL137001R1210	0.270				
							0 1	AF09-30-01-12	15BL137001R1201	0.270			
				100...250	100...250	1 0	AF09-30-10-13	15BL137001R1310	0.270				
							0 1	AF09-30-01-13	15BL137001R1301	0.270			
				250...500	250...500	1 0	AF09-30-10-14	15BL137001R1410	0.310				
							0 1	AF09-30-01-14	15BL137001R1401	0.310			
				5.5	28	7.5	28	24...60	20...60 (1)	1 0	AF12-30-10-11	15BL157001R1110	0.270
											0 1	AF12-30-01-11	15BL157001R1101
								48...130	48...130	1 0	AF12-30-10-12	15BL157001R1210	0.270
											0 1	AF12-30-01-12	15BL157001R1201
								100...250	100...250	1 0	AF12-30-10-13	15BL157001R1310	0.270
											0 1	AF12-30-01-13	15BL157001R1301
								250...500	250...500	1 0	AF12-30-10-14	15BL157001R1410	0.310
											0 1	AF12-30-01-14	15BL157001R1401
7.5	30	10	30					24...60	20...60 (1)	1 0	AF16-30-10-11	15BL177001R1110	0.270
											0 1	AF16-30-01-11	15BL177001R1101
								48...130	48...130	1 0	AF16-30-10-12	15BL177001R1210	0.270
											0 1	AF16-30-01-12	15BL177001R1201
								100...250	100...250	1 0	AF16-30-10-13	15BL177001R1310	0.270
											0 1	AF16-30-01-13	15BL177001R1301
								250...500	250...500	1 0	AF16-30-10-14	15BL177001R1410	0.310
											0 1	AF16-30-01-14	15BL177001R1401
				11	45	15	45	24...60	20...60 (1)	0 0	AF26-30-00-11	15BL237001R1100	0.310
											0 0	AF26-30-00-12	15BL237001R1200
								48...130	48...130	0 0	AF26-30-00-13	15BL237001R1300	0.310
											0 0	AF26-30-00-14	15BL237001R1400
								100...250	100...250	0 0	AF26-30-00-11	15BL277001R1100	0.310
											0 0	AF26-30-00-12	15BL277001R1200
								250...500	250...500	0 0	AF26-30-00-13	15BL277001R1300	0.310
											0 0	AF26-30-00-14	15BL277001R1400
15	50	20	50	24...60	20...60 (1)	0 0	AF30-30-00-11	15BL297001R1100	0.310				
							0 0	AF30-30-00-12	15BL297001R1200	0.310			
				48...130	48...130	0 0	AF30-30-00-13	15BL297001R1300	0.310				
							0 0	AF30-30-00-14	15BL297001R1400	0.350			
				100...250	100...250	0 0	AF30-30-00-11	15BL297001R1100	0.310				
							0 0	AF30-30-00-12	15BL297001R1200	0.310			
				250...500	250...500	0 0	AF30-30-00-13	15BL297001R1300	0.310				
							0 0	AF30-30-00-14	15BL297001R1400	0.350			
18.5	50	25	50	24...60	20...60 (1)	0 0	AF38-30-00-11	15BL297001R1100	0.310				
							0 0	AF38-30-00-12	15BL297001R1200	0.310			
				48...130	48...130	0 0	AF38-30-00-13	15BL297001R1300	0.310				
							0 0	AF38-30-00-14	15BL297001R1400	0.350			
				100...250	100...250	0 0	AF38-30-00-11	15BL297001R1100	0.310				
							0 0	AF38-30-00-12	15BL297001R1200	0.310			
				250...500	250...500	0 0	AF38-30-00-13	15BL297001R1300	0.310				
							0 0	AF38-30-00-14	15BL297001R1400	0.350			

(1) AF...-30-...-11 not suitable for direct control by PLC-output.



Main dimensions mm, inches