

# LPS Series 120W

## AC-DC DIN Rail Power Supplies



### Key Features

- 12, 24 & 48 VDC
- Universal Input: 90-264VAC / 120-375VDC
- High Efficiency
- Short Circuit Protection
- Internal Input Filter
- IP20 Protection Rated




### Technical Specification - 120W Output

Model	LPS-1-120-12DC	LPS-1-120-24DC	LPS-1-120-48DC
Input Voltage	90-264VAC / 127-375VDC		
Output Wattage	120W		
Output Voltage / Power Dissipation	12VDC / 24W	24VDC / 20W	48VDC / 19W
Output Current	10A	5A	2.5A
Efficiency	85.5%	88%	89%
<b>General Specification</b>			
Approval	cURus		
Isolation Voltage	3000VAC/4242VDC		
Isolation Resistance	100MΩ @ 500VDC		
Ambient Temperature	-20 to +70°C		
Derating	(61 to 71°C) 2.5%/°C		
Storage Temperature	-40 to +85°C		
Relative Humidity	10 to 95% RH		
Cooling	Free air convection		
Dimensions	L125 x W40 x D113 (126.5 inc. DIN rail mount) mm		
Weight	600g		
Case Material	Metal		
<b>Input Specifications</b>			
Rated Input Voltage	115 - 230VAC (auto select)		
Input Voltage Range	90-264VAC, 127-375VDC		
Line Frequency	50/60Hz		
Power Factor @ 115VAC	0.55 Typical (0.58 Measured)		
Power Factor @ 230VAC	0.70 Typical (0.75 Measured)		
Inrush Current (115 / 230VAC)	20 / 35A		
<b>Output Specifications</b>			
Output Voltage Accuracy	±1%		
Minimum Load	0%		
Line Regulation	±0.5%		
Load Regulation	±1%		
Turn On Time	1000ms after AC applied to input at full resistive load		
Voltage Fall Time	150ms		
Voltage Rise Time	150ms		
Hold Up Time (115 / 230VAC)	10 / 16ms		
Temperature Coefficient	±0.03%/°C		
Ripple & Noise	120mVp-p		
Voltage Trim Range	11.4 ~ 14.5VDC	22.5 ~ 28.5VDC	45 ~ 55VDC
DC ON & LOW Indicator (Green & Red LED)	10 ~ 11.2VDC	17.6 ~ 19.4VDC	37 ~ 43VDC
<b>Control &amp; Protection</b>			
Rated Overload Protection	105-130%		
Over Voltage Protection	14-17VDC	29-33VDC	50-65VDC
Output Short Circuit	Fold Forward		

# LPS Series 120W AC-DC DIN Rail Power Supplies



## Dimensions (mm)



## Pin Connections

Input		Output	
Pin No.	Description	Pin No.	Description
1	FG $\oplus$	1, 2	DC OUTPUT V-
2	AC / N	3, 4	DC OUTPUT V+
3	AC / L		

## Installation

### Ventilation / Cooling

Normal convection  
All sides 25mm free space  
For cooling recommended


### Connector Size Range

AWG24-10 (0.2 ~ 4mm<sup>2</sup>) flexible / solid cable,  
- Input connector can withstand torque at maximum 9 pound-inches  
- Output connector can withstand torque at maximum 5.5 pound-inches  
8 m/m stripping cable end recommends  
Use copper conductors only, 60 / 75°C


## Construction

Easy snap-on mounting onto the DIN-Rail (TS35/7.5 or TS35/15), unit sits safely and firmly on the rail.


## Derating Curve



## Minus Output & Input Voltage Curves



## Circuit Schematic



# LPS Series 240W AC-DC DIN Rail Power Supplies



## Key Features

- 24 & 48 VDC
- Universal Input: 90-264VAC / 120-375VDC
- High Efficiency
- Short Circuit Protection
- Internal Input Filter
- IP20 Protection Rated




## Technical Specification - 240W & 300W Output

Model	LPS-1-240-24DC	LPS-1-240-48DC
Input Voltage	90-264VAC / 120-375VDC	
Output Wattage	240W	240W
Output Voltage / Power Dissipation	24VDC / 35W	48VDC / 32W
Output Current	10A	5A
Efficiency	85.5%	90%
<b>General Specification</b>		
Approval	cURus	
Isolation Voltage	3000VAC/4242VDC	
Isolation Resistance	100MΩ @ 500VDC	
Ambient Temperature	-20 to +70°C	
Derating	(55 to 70°C) 2.5%/°C	
Storage Temperature	-40 to +85°C	
Relative Humidity	10 to 95% RH	
Cooling	Free air convection	
Dimensions	L125 x W63 x D113.5 (127 inc. DIN rail mount) mm	
Weight	1000g	
Case Material	Metal	
<b>Input Specifications</b>		
Rated Input Voltage	115-230VAC	
Input Voltage Range	90-264VAC, 127-375VDC	
Line Frequency	50/60Hz	
Power Factor @ 115VAC	0.6 Typical (0.61 Measured)	
Power Factor @ 230VAC	0.75 Typical (0.77 Measured)	
Inrush Current (115 / 230VAC)	20 / 35A	
<b>Output Specifications</b>		
Output Voltage Accuracy	±1%	
Minimum Load	0%	
Line Regulation	±0.5%	
Load Regulation	±1%	
Turn On Time	1000ms after AC applied to input at full resistive load	
Voltage Fall Time	150ms	
Voltage Rise Time	150ms	
Hold Up Time (115 / 230VAC)	10 / 16ms	
Temperature Coefficient	±0.03%/°C	
Ripple & Noise	150mVp-p	
Voltage Trim Range	22.5-28.5VDC	47-56VDC
<b>Control &amp; Protection</b>		
Rated Overload Protection	105-130%	
Over Voltage Protection	29-33VDC	56-65VDC
Output Short Circuit	Shutdown Output Voltage with Auto Recovery	

# LPS Series 240W AC-DC DIN Rail Power Supplies



## Dimensions (mm)



## Pin Connections

Input		Output	
Pin No.	Description	Pin No.	Description
1	FG ⊕	1, 2	DC OUTPUT V-
2	AC / N or DC-	3, 4	DC OUTPUT V+
3	AC / L or DC+		

## Installation


**Ventilation / Cooling**  
Normal convection  
All sides 25mm free space  
For cooling recommended

**Connector Size Range**  
AWG24-10 (0.2 ~ 4mm<sup>2</sup>) flexible / solid cable,  
- Input connector can withstand torque at maximum 9 pound-inches  
- Output connector can withstand torque at maximum 5.5 pound-inches  
8 m/m stripping cable end recommends  
Use copper conductors only, 60 / 75°C


## Construction

Easy snap-on mounting onto the DIN-Rail (TS35/7.5 or TS35/15), unit sits safely and firmly on the rail.

## Derating Curve



## Minus Output & Input Voltage Curves



## Circuit Schematic

