

Splitting multigates for cables with attached connectors

Often with the cables come the connectors and very often the connectors can not be removed and re-attached. The delicate data cables, HDMI's etc. are difficult or impossible to re-join at site. The splitting multigate is the solution that lets the cables be installed with the connectors and on top of that the cables can be changed as often as wanted. Choose splitting multigate for fast, safe and versatile installations.

Splitting multigates SCG and MC are intended for leading through both low and medium power current cables, but also various kinds of tubing.

Splitting multigates SCG and MC are new type of metal and plastic reinforced multigate made of different types of polymers (TPE and PP-GF). *Look more about materials at Comparison of materials on page 95.*

They meet the requirements of IP55 protection class without the need of any additional gaskets or grommets. This makes it very easy to use and provides many benefits for compact installation unit.

Splitting multigates SCG and MC are suitable for both in- and outdoor application and operating temperature range is from -40 °C to +90 °C.



SCG 1x3-35 (IP55)



MC 1x8-67 (IP55)



MC 1/9 (IP55)


Black UL 94 V-0	●	MBA4N01B11	MBA4N19B11	MBA4N12B11
Black	●	-	MBA4N18B11	-

Technical data				
Service temperature		-40 - +90	-40 - +90	-40 - +90
Dimensions (A / B / C) (mm)		77 / 60 / 40	123 / 93 / 75	123 / 93 / 75
Number of cables (pcs) x cable diameter (mm)		1 x 3-35	1 x 8-67	2 x 8-11 2 x 10-13 5 x up to 14*
Total number of cables		1	1	9
Mounting hole size		SCG 1	MC 1	MC 1
Weight (g)		160	870	568
Package (pcs)		100	15	20




* Only for cables without connectors

Dimensions

SCG 1



MC 1





SCG 2x3-35 (IP55)

MC 2x8-67 (IP55)

MC 2/10 (IP55)

MC 2/18 (IP55)

	●	MBA4N02B11	MBA4N28B11	MBA4N21B11	MBA4N22B11
Black UL 94 V-0	●				
Technical data					
Service temperature		-40 - +90	-40 - +90	-40 - +90	-40 - +90
Dimensions (A / B / C) (mm)		136 / 60 / 40	222 / 93 / 75	222 / 93 / 75	222 / 93 / 75
Number of cables (pcs) x cable diameter (mm)		2 x 3-35	2 x 8-67	1 x 8-67 2 x 8-11 2 x 10-13 5 x up to 14*	4 x 8-11 4 x 10-13 10 x up to 14*
Total number of cables		2	2	10	18
Mounting hole size		SCG 2	MC 2	MC 2	MC 2
Weight (g)		263	870	680	976
Package (pcs)		50	15	15	10

* Only for cables without connector

Dimensions

