

Model: YH605G



RoHS

Overview

Industrial Ethernet switch, 5 Port 10/100/1000Mbps ports , for connecting with devices like computer, switch, hub, server, etc, as well as Ethernet camera, industrial VoIP phone, wireless AP .

Specially designed for harsh outdoor applications. Its 3KV network port surge protection can adapt to harsh outdoor environment and ensure the reliability of the uninterrupted PoE system. Ethernet input also chooses industry-standard types of Ethernet



Features

- 5 Port 10/100/1000Mbps
- Automatic MAC address learning and aging
- Automatically support IGMP (Multicasting)
- 10/100/1000Mbps Auto-negotiation , auto-MDI-MDI-X
- LED indicators for monitoring Ethernet/link/activity
- Supports 10/100/1000Mbps-Full/Half-duplex
- Supports DIN-Rail installation
- Supports Daisy-Chain connection
- Supports Broadcast Storm Control
- Super lightning protection, IP40 protection.
- Excellent heat elimination without cooling fan.
- Redundant dual DC Powerinputs.
- Apply to Urban Intelligent Traffic Monitoring System (ITS), Safe City.
- Harsh industrial environment or higher requirement
- 6KV port Lightning protection
- -40°C~+85°C operating temperature range.
- 5-Year Warranty



Technical Specification

Product Name	5 Port 10/100/1000M Industrial Switch
Product Model	YH605G
Interface	4x10/100/1000Base-T port + 1 port 1000Base Uplink
Network Protocols	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T;IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z ; IEEE802.3x;
Network Media	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-TX: Cat6 or later UTP(≤100 meter)
Performance Specification	Bandwidth: 10Gbps Packet Buffer Memory:2M Packet Forwarding Rate:1488000pps/port MAC Address Table: 4K
Forwarding Mode	Store-and-Forward
Protection	Lightening protection, IP40 protection
LED Indicators	Ethernet: PWR; Link; Link/Act
Ethernet Supply	Input Voltage: DC12~48V /Terminal block



Other Specifications	
Working Environment	Working temperature: -40~+85°C ; Storage temperature: -45~+85°C Relative Humidity: 5%~95 %(no condensation)
Industry Standard	FCC CFR47 Part 15,EN55022/CISPR22, Class A EMS: IEC61000-4-2 (ESD): ± 8kV (contact), ± 15kV (air) IEC61000-4-3 (RS): 10V/m (80MHz-2GHz) IEC61000-4-4 (EFT): Ethernet Port: ± 4kV; Data Port: ± 2kV IEC61000-4-5 (Surge): Ethernet Port: ± 2kV/DM, ± 4kV/CM; Data Port: ± 2kV IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz) IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
Shell	IP40 protect grade, metal shell
Installation	DIN-Rail
Packing List	1× Industrial Switch (plus terminal block) 1× User Manual/Certificate of quality/Warranty card 1× DIN-Rail mounting kit
Certification	CE mark, commercial; FCC Part 15 Class B; VCCI Class B EN 55022 (CISPR 22), Class B
MTBF	300,000 hours
Weight & Size	Product Weight: 0.36KG Packing Weight: 0.6KG Product size (L× W× H): 128mm× 86mm× 34mm Packing size(L× W× H): 220mm× 22mm× 67mm
Warranty	5-years